SONY

XM-SD51X

Amplifier

Key Features

- 1100W max power
- 250W x 1 RMS into 4 ohms, 20Hz - 300Hz @ 1.0% THD
- 500W x 1 RMS into 2 ohms, 20Hz - 300Hz @ 1.0% THD
- Subsonic filter (15 Hz)
- Remote subwoofer level control
- Variable 50 - 300 Hz low pass filter
- 1100W max power
- 250W x 1 RMS into 4 ohms, 20Hz - 300Hz @ 1.0% THD
- 500W x 1 RMS into 2 ohms, 20Hz - 300Hz @ 1.0% THD
- Subsonic filter (15 Hz)
- Remote subwoofer level control
- Variable 50 - 300 Hz low pass filter
- 40 Hz EQ boost
- MOSFET output stage & power supply
- RCA & speaker level inputs
- Line level thru-put
- 2-Year limited warranty
- CEA-2006 Power Compliant

Specifications

Audio

Frequency Response: 5-300 Hz

Input Level: 6.5 - 16.0V (Speaker level input)

Noise Level: Signal to noise ratio (dB)- 76

Power

Power Consumption (in Operation): 1100 Watts

Output Power: Bridged into 4 ohms, THD%- N/A

Current Drain: 55A

Output Voltage: 10.5 - 16V

Dimensions

Weight: 9 lbs, 15 oz (4.5 Kg)

Measurements: 11 x 2 1/4 x 15 7/8" (279 x 57 x 403mm)

UPC Code: 027242664777

SONY

XM-SD51X

Amplifier

Please visit the Dealer Network for more information at www.sony.com/dn

©2006 Sony Electronics Inc.
Reproduction in whole or in part without written permission is prohibited.
Sony is a trademark of Sony. All other trademarks are property of their respective owners.
Features and specifications are subject to change without notice. Non-metric weights and measures are approximate.